

(19) World Intellectual Property
Organization
International Bureau



21 DEC 2004



(43) International Publication Date
22 January 2004 (22.01.2004)

PCT

(10) International Publication Number
WO 2004/008565 A2

(51) International Patent Classification⁷: **H01M 8/02**

(21) International Application Number:
PCT/CA2003/000920

(22) International Filing Date: 18 June 2003 (18.06.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/394,921 10 July 2002 (10.07.2002) US

(71) Applicant (*for all designated States except US*): DUPONT
CANADA INC. [CA/CA]; 7070 Mississauga Road, Mis-
sissauga, Ontario L5M 2H3 (CA).

(72) Inventors; and

(75) Inventors/Applicants (*for US only*): CAI, Yuqi [CA/CA];
252 Waterloo Drive, Kingston, Ontario K7M 8P2 (CA).
CHOPRA, Divya [IN/CA]; 62 Old Oak Road, Apt. 408,
Kingston, Ontario K7M 6X3 (CA). PETERS, Jay, A.

[CA/CA]; 1827 Westgrove Drive, Brights Grove, Ontario
N0N 1C0 (CA). WALLER, Michael [CA/CA]; 481
Regency Crescent, Waterloo, Ontario N0N 1C0 (CA).
XIE, Tuyu [CA/CA]; 944 Nottingham Avenue, Kingston,
Ontario K7P 2B8 (CA).


(74) Agents: CLARIZIO, Dino, P. et al.; Dimock Stratton
Clarizio, 20 Queen Street West, Suite 3202, Box 102,
Toronto, Ontario M5H 3R3 (CA).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC,
SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG,
US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,

[Continued on next page]

(54) Title: ELASTOMERIC SEPARATOR PLATES AND METHOD OF FABRICATION



(57) Abstract: An electrically conductive flow field separator plate is disclosed for use in a proton exchange membrane fuel cell. The plate comprises a frame portion, a central planar portion within the frame and a flow field formed in a surface of the central planar portion. The frame portion is elastomeric so as to form a seal with adjacent fuel cell components thereby eliminating the use of separate sealing elements. The frame and the central planar portion are of unitary construction and comprise from about 10 wt.% to about 50 wt.% of elastomer and from about 50 wt.% to about 90 wt.% of conductive filler.

BEST AVAILABLE COPY

WO 2004/008565 A2